

MOBILE - DIGITAL

The power you need to image
any size patient



Features

- 50kW (40-150 kVp) High Frequency X-ray Generator
- Onboard PC with 17 inch touch screen interface
- Available with your choice of Canon or Vieworks Wireless detector
- Secondary drive controls on tube handle for quick positioning without needing to return to the main console with precision positioning buttons on the handles of the tube arm
- Narrow width makes it ideal for navigating through and in small spaces
- Two battery systems provide independent power for exposure control and the drive system to reduce power drain

System Specifications:

- **Tube arm reach** 49.2 in. (1,250 mm)
Column rotation: $\pm 315^\circ$
- **Maximal SID to floor** 80.7 in. (2,050 mm)
- **Minimal SID to floor** 21.6 in. (550 mm)
- **Weight** 1,312 lbs (595 kg)
- **Size** (L x W x H) 53.54 in. x 26.4 in. x 77.9 in. (1,360 mm x 670 mm x 1,980 mm)
- **Frontal Anti-collision system**

Generator Specifications:

- **kW rating** 50 kW
- **kVp range** 40 to 150 kVp
- **18 mA stations:** 10 - 500 mA selectable
- **Exposure time range** 0.001 - 10 sec
mAs range 0.1 - 500 mAs
- **Line requirements** Single phase line regulation from 100 - 240 Vac (+/-10%)





MOBILE - ANALOG

Mobile power for use with your current (Film, CR or DR) imaging solution

The most powerful x-ray mobile system in the market, now with telescopic column for increased visibility during moving.

Features

- 50kW (40-150 kVp) High Frequency X-ray Generator
- Onboard PC with 17" touch screen interface
- Secondary drive controls on tube handle for quick positioning without needing to return to the main console with precision positioning buttons on the handles of the tube arm
- Narrow width makes it ideal for navigating through and in small spaces
- Two battery systems provide independent power for exposure control and the drive system to reduce power drain

System Specifications:

- **Tube arm reach** 49.2 in. (1,250 mm)
Column rotation: $\pm 315^\circ$
- **Maximal SID to floor** 80.7 in. (2,050 mm)
- **Minimal SID to floor** 21.6 in. (550 mm)
- **Weight** 1,312 lbs (595 kg)
- **Size (L x W x H)** 53.54 in. x 26.4 in. x 77.9 in. (1,360 mm x 670 mm x 1,980 mm)
- **Frontal Anti-collision system**

Generator Specifications:

- **kW rating** 50 kw
- **kVp range** 40 to 150 kVp
- **18 mA stations:** 10 - 500 mA selectable
- **Exposure time range** 0.001 - 10 sec
mAs range 0.1 - 500 mAs
- **Line requirements** Single phase line regulation from 100 - 240 Vac (+/-10%)

